

MATERIAL SAFETY DATA SHEET

17-600 -- DELUX INTERIOR LATEX FLAT Printed: 08/03/07 Revised: 02/07/02 Page 1

----- HMIS CODES -----

Hazard Rating:	Health	1
Least --> Greatest	Flammability	0
0 --> 4	Reactivity	0
	Personal Protection	B

Manufacturer: ASSOCIATED PAINT  
10160 NW SOUTH RIVER DRIVE  
MEDLEY, FL 33178  
Phone: 305-885-1964

EMERGENCY TELEPHONE: 305-558-7315

SECTION I: PRODUCT IDENTIFICATION

Product Code: 17-600 Product Class: PAINT  
Product Name: 17-600 DELUX INTERIOR FLAT  
Chemical Name: DELUX INTERIOR LATEX FLAT CAS Number: NA

SECTION IIA: HAZARDOUS INGREDIENTS

Ingredient	CAS Number	(To Nearest 1.00%) % by Wt.	Vapor % by Vol.	LEL Press.
0.				

NA = Not Applicable; NE = Not Established

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

Ingr. #	-----OSHA PEL's-----		-----ACGIH TLV's-----		
	OSHA ppm	OSHA mg/m3	TWA ppm	TWA mg/m3	STEL ppm
0.					

NA = Not Applicable; NE = Not Established

SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 212.00 - 220.00 Pounds per Gallon: 11.15  
Vapor Density: LIGHTER THAN AIR Evaporation Rate: SLOWER THAN ETHER  
Solubility in Water: S  
Appearance: WHITE OR COLORED LIQUID

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:  
OSHA: 0 DOT: NA  
Flash Point: NA (Method: Na)  
UEL: NA

Extinguishing Media: FOAM,CO2,DRYCHEMICAL

Unusual Fire and Explosion Hazards  
MATERIAL MAY SPLATTER ABOVE 212 DGS.F.SEALED CONTAINERS MAY EXPLODE WHEN EX-  
POSED TO EXTREME HEAT.

Special Firefighting Procedures  
POLYMER FILM CAN BURN.AVOID BREATHING FUMES,TRACE AMOUNTS OF CARBON DIOXIDE-  
CARBON MONOXIDE MAY BE RELEASED.COOL CONTAINERS WITH WATER.

MATERIAL SAFETY DATA SHEET

17-600 -- DELUX INTERIOR LATEX FLAT Printed: 08/03/07 Revised: 02/07/02 Page 2

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure  
HEADACHE, NAUSEA, AND IRRITATION OF NOSE, THROAT, AND LUNGS.

Medical Conditions Prone to Aggravation by Exposure  
NONE KNOWN

Primary Routes of Entry into the Body, and Effects  
INHALATION, SKIN, EYES, AND, SWALLOWING.

EMERGENCY FIRST-AID PROCEDURES

EYE AND SKIN CONTACT: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN. WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: MOVE SUBJECT TO FRESH AIR.

SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization WILL NOT OCCUR.

Hazardous Decomposition Products  
CARBON DIOXIDE/CARBON MONOXIDE

Conditions to Avoid  
NONE KNOWN

Incompatibilities (Materials to Avoid)  
NONE KNOWN

SECTION VII: SPILL OR LEAK PROCEDURES; WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled  
AVOID CONTACT. SOAK UP WITH ABSORBENT MATERIAL. KEEP SPILLS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

Waste Disposal Methods  
DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection  
DUST AND MIST MASK SUCH AS TC-21C-141 OR TC-21C-183 FOR PARTICULATE DUST PROTECTION.

Ventilation  
MECHANICAL EXHAUST MAY BE REQUIRED IN CONFINED AREAS.

Protective Gloves  
RUBBER GLOVES REQUIRED FOR PROLONGED CONTACT.

Eye Protection  
GOGGLES CAPABLE OF PROTECTION AGAINST SPLASH OR SPRAY (ANZI Z87 OR EQUAL).

Page 2

DELUX INTERIOR LATEX FLAT

Revision Date: 02/07/02

MATERIAL SAFETY DATA SHEET

Other Protective Equipment  
USUALLY NOT REQUIRED.

Hygienic Practices  
NORMAL HYGIENIC PRACTICES SHOULD BE FOLLOWED.

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing  
KEEP IN AREA WITH TEMPERATURES NOT BELOW 50 DGS.F.OR ABOVE 100 DGS.F.KEEP  
CONTAINERS LABELED.KEEP OUT OF THE REACH OF CHILDREN.

Other Precautions  
NONE KNOWN.

Disclaimer:THIS INFORMATION IS BASED ON TECHNICAL DATA BELIEVED TO BE ACCURATE  
AND RELIABLE,BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.

END OF MSDS

**24 Hour Emergency Contact Information:**  
**1 - (800) - 255-3924 U.S.A. & Canada**  
**Outside the U.S.A.**  
**Country Code call originating from then + 01-813-248-0585**