

MATERIAL SAFETY DATA SHEET

DURA-STAINWH -- CONCRETE STAIN WHITE Printed: 10/22/07 Revised: 08/10/06 Page 1

		----- HMIS CODES -----
	Hazard Rating:	Health 2
	Least --> Greatest	Flammability 3
Manufacturer:	0 --> 4	Reactivity 0
ASSOCIATED PAINT		Personal Protection J
10160 NW SOUTH RIVER DRIVE		
MEDLEY, FL 33178		
Phone: 305-885-1964	EMERGENCY TELEPHONE:	305-558-7315

SECTION I: PRODUCT IDENTIFICATION

Product Code: DURA-STAINWH Product Class: PAINT  
 Product Name: CONCRETE STAIN WHITE  
 Chemical Name: CONCRETE STAIN WHITE CAS Number:

SECTION IIA: HAZARDOUS INGREDIENTS

		(To Nearest .01%)	Vapor
Ingredient	CAS Number	% by Wt.	% by Vol. LEL Press.
1. XYLOL	1330-20-7	56.83	72.85 1.0 9.00
		NA = Not Applicable; NE = Not Established	

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

	-----OSHA PEL's-----	-----ACGIH TLV's-----
Ingr. #	OSHA ppm OSHA mg/m3	TWA ppm TWA mg/m3 STEL ppm STEL mg/m3
1.	100 NA	100 NA 150 NA
		NA = Not Applicable; NE = Not Established

SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 279.00 - 285.00 Pounds per Gallon: 9.27  
 Vapor Density: HEAVIER THAN AIR Evaporation Rate: FASTER THAN ETHER  
 Solubility in Water: NO  
 Appearance:

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:  
 OSHA: 3 DOT: 2  
 Flash Point: 40.00 (Method: Tcc)  
 UEL: 7.1

Extinguishing Media: WATER SPRAY, DRY CHEMICAL, ALCOHOL FOAM, ALL PURPOSE  
 AFFF, CO2.

Unusual Fire and Explosion Hazards  
 VAPORS MAY FORM EXPLOSIVE MIXTURE WITH AIR. VAPORS CAN TRAVEL TO A SOURCE OF  
 IGNITION AND FLASH BACK.

Special Firefighting Procedures  
 EXPLOSION HAZARD IF EXPOSED TO EXTREME HEAT OR THERMAL SHOCK.

MATERIAL SAFETY DATA SHEET

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure

ACUTE OR CHRONIC OVEREXPOSURE MAY CAUSE SYSTEMATIC TOXICITY, INCLUDING ADVERSE EFFECTS TO THE:KIDNEY,LIVER,BRAIN,BLOOD,SPLEEN,TESTES,PITUATARY,THYROID,RESPIRATORY AND CENTRAL NERVOUS SYSTEMS.

Medical Conditions Prone to Aggravation by Exposure

DISORDERS OF THE EYE,SKIN,KIDNEY,LIVER,BLOOD,RESPIRATORY,CARDIO-VASCULAR NEUROLOGICAL AND HEMOPOIETIC SYSTEMS.

Primary Routes of Entry into the Body, and Effects

INHALATION,INGESTION,SKIN AND EYE CONTACT.

EMERGENCY FIRST-AID PROCEDURES

SKIN:IMMEDIATELY WASH WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING.GET MEDICAL ATTENTION IF IRRITATION DEVELOPES OR PERSISTS.

EYE:FLUSH IMMEDIATELY WITH LARGE AMOUNTS OF WATER FOR 15 MINUTES. GET MEDICAL ATTENTION IF IRRITATION PERSISTS.

SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization WILL NOT OCCUR.

Hazardous Decomposition Products

COX,NOX AND SOX

Conditions to Avoid

AVOID FREE FALL,OPEN FLAME,IGNITION SOURCES,OXIDIZERS.DO NOT CUT,GRIND,DRILL,OR WELD EMPTY CONTAINERS.

Incompatibilities (Materials to Avoid)

STRONG OXIDIZERS.

SECTION VII: SPILL OR LEAK PROCEDURES; WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled

ELIMINATE AND/OR SHUT OFF SOURCES OF IGNITION.ISOLATE AREA.ABSORB SPILLS WITH INERT MATERIAL.PLACE IN CLOSED CONTAINER.

Waste Disposal Methods

DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection

USE NIOSH/MSHA APPROVED RESPIRATOR.

Ventilation

VENTILATE TO MOVE AIR AND AVOID CONCENTRATION OF VAPORS.

MATERIAL SAFETY DATA SHEET

Protective Gloves

USE APPROPRIATE CHEMICAL PROTECTIVE GLOVES.

Eye Protection

WEAR SAFETY GOGGLES TO AVOID EYE CONTACT.

Other Protective Equipment

EYE WASH FACILITY

Hygienic Practices

WASH SKIN IMMEDIATELY AFTER USE OR BEFORE EATING.

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing

STORE IN TIGHTLY CLOSED CONTAINERS IN A COOL, DRY, ISOLATED, VENTILATED AREA AWAY FROM HEAT, IGNITION SOURCES AND STRONG OXIDIZERS. DO NOT SMOKE OR DRINK IN AREAS OF USE AND STORAGE.

Other Precautions

INHALATION OF THE VAPORS OF THIS PRODUCT HAVE BEEN KNOWN TO CAUSE BRAIN DAMAGE AND/OR DEATH.

Disclaimer: THIS INFORMATION IS BASED ON TECHNICAL DATA BELIEVED TO BE ACCURATE AND RELIABLE, BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.

END OF MSDS

24 Hour Emergency Contact Information:  
1 - (800) - 255-3924 U.S.A. & Canada  
Outside the U.S.A.  
Country Code call originating from then + 01-813-248-0585