

MATERIAL SAFETY DATA SHEET

25-600 -- ACRYLIC LATEX SEMIGLOSS Printed: 09/11/07 Revised: 02/08/02 Page 1

		----- HMIS CODES -----
	Hazard Rating:	Health 1
	Least --> Greatest	Flammability 0
Manufacturer:	0 --> 4	Reactivity 0
ASSOCIATED PAINT		Personal Protection B
10160 NW SOUTH RIVER DRIVE		
MEDLEY, FL 33178		
Phone: 305-885-1964	EMERGENCY TELEPHONE:	305-558-7315

SECTION I: PRODUCT IDENTIFICATION

Product Code: 25-600 Product Class: PAINT
 Product Name: 25-600 LATEX S/G WHITE
 Chemical Name: ACRYLIC LATEX SEMIGLOSS CAS Number: NA

SECTION IIA: HAZARDOUS INGREDIENTS

		(To Nearest 1.00%)	Vapor
Ingredient	CAS Number	% by Wt.	% by Vol. LEL Press.
1. ETHYLENE GLYCOL	107-21-1	4.00	5.00 3.2 -.10
		NA = Not Applicable; NE = Not Established	

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

	----OSHA PEL's-----	-----ACGIH TLV's-----
Ingr. #	OSHA ppm OSHA mg/m3	TWA ppm TWA mg/m3 STEL ppm STEL mg/m3
1.	50 NE	NE 100.00 100 100.00
		NA = Not Applicable; NE = Not Established

SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 212.00 - 220.00 Pounds per Gallon: 10.39
 Vapor Density: LIGHTER THAN AIR Evaporation Rate: SLOWER THAN ETHER
 Solubility in Water: S
 Appearance: WHITE OR COLORED LIQUID

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:
 OSHA: 0 DOT: NA
 Flash Point: NA (Method: Na)
 UEL: NA

Extinguishing Media: FOAM,CO2,DRYCHEMICAL

Unusual Fire and Explosion Hazards
 MATERIAL MAY SPLATTER ABOVE 212 DGS.F.SEALED CONTAINERS MAY EXPLODE WHEN EX-
 POSED TO EXTREME HEAT.

Special Firefighting Procedures
 POLYMER FILM CAN BURN.AVOID BREATHING FUMES,TRACE AMOUNTS OF CARBON DIOXIDE-
 CARBON MONOXIDE MAY BE RELEASED.COOL CONTAINERS WITH WATER.

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure

HEADACHE, NAUSEA, AND IRRITATION OF NOSE, THROAT, AND LUNGS.

Medical Conditions Prone to Aggravation by Exposure

NONE KNOWN

Primary Routes of Entry into the Body, and Effects

INHALATION, SKIN, EYES, AND, SWALLOWING.

EMERGENCY FIRST-AID PROCEDURES

EYE AND SKIN CONTACT: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN. WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: MOVE SUBJECT TO FRESH AIR.

SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization WILL NOT OCCUR.

Hazardous Decomposition Products

CARBON DIOXIDE/CARBON MONOXIDE

Conditions to Avoid

NONE KNOWN

Incompatibilities (Materials to Avoid)

NONE KNOWN

SECTION VII: SPILL OR LEAK PROCEDURES; WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled

AVOID CONTACT. SOAK UP WITH ABSORBENT MATERIAL. KEEP SPILLS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

Waste Disposal Methods

DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection

DUST AND MIST MASK SUCH AS TC-21C-141 OR TC-21C-183 FOR PARTICULATE DUST PROTECTION.

Ventilation

MECHANICAL EXHAUST MAY BE REQUIRED IN CONFINED AREAS.

Protective Gloves

RUBBER GLOVES REQUIRED FOR PROLONGED CONTACT.

Eye Protection

GOGGLES CAPABLE OF PROTECTION AGAINST SPLASH OR SPRAY (ANZI Z87 OR EQUAL).

=====
Other Protective Equipment
USUALLY NOT REQUIRED.

Hygienic Practices
NORMAL HYGIENIC PRACTICES SHOULD BE FOLLOWED.

SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing
KEEP IN AREA WITH TEMPERATURES NOT BELOW 50 DGS.F.OR ABOVE 100 DGS.F.KEEP
CONTAINERS LABELED.KEEP OUT OF THE REACH OF CHILDREN.

Other Precautions
NONE KNOWN.

Disclaimer:THIS INFORMATION IS BASED ON TECHNICAL DATA BELIEVED TO BE ACCURATE
AND RELIABLE,BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.
=====

END OF MSDS
=====

24 Hour Emergency Contact Information:
1 - (800) - 255-3924 U.S.A. & Canada
Outside the U.S.A.
Country Code call originating from then + 01-813-248-0585