

MATERIAL SAFETY DATA SHEET

00-300 -- DO NOT USE-USE 00-300R Printed: 09/11/07 Revised: 09/16/02 Page 1

		----- HMIS CODES -----	
	Hazard Rating:	Health	1
	Least --> Greatest	Flammability	0
Manufacturer:	0 --> 4	Reactivity	0
ASSOCIATED PAINT		Personal Protection	B

10160 NW SOUTH RIVER DRIVE  
MEDLEY, FL 33178  
Phone: 305-885-1964

EMERGENCY TELEPHONE: 305-558-7315

SECTION I: PRODUCT IDENTIFICATION

Product Code: 00-300	Product Class: PAINT
Product Name: DO NOT USE-USE 00-300R	
Chemical Name: DO NOT USE-USE 00-300R	CAS Number: NA

SECTION IIA: HAZARDOUS INGREDIENTS

		(To Nearest 1.00%)	Vapor
Ingredient	CAS Number	% by Wt.	% by Vol. LEL Press.
1. ETHYLENE GLYCOL	107-21-1	1.00	1.00 3.2 -.10

NA = Not Applicable; NE = Not Established

SECTION IIB: OCCUPATIONAL EXPOSURE LIMITS

	----OSHA PEL's-----	-----ACGIH TLV's-----
Ingr. #	OSHA ppm OSHA mg/m3	TWA ppm TWA mg/m3 STEL ppm STEL mg/m3
1.	50 NE	NE 100.00 100 100.00

NA = Not Applicable; NE = Not Established

SECTION III: PHYSICAL DATA

Boiling Range (degrees F): 212.00 - 220.00 Pounds per Gallon: 9.52  
Vapor Density: LIGHTER THAN AIR Evaporation Rate: SLOWER THAN ETHER  
Solubility in Water: S  
Appearance:

SECTION IV: FIRE AND EXPLOSION HAZARD DATA

Flammability Classification:  
OSHA: 0 DOT: NA  
Flash Point: NA (Method: Na)  
UEL: NA

Extinguishing Media: FOAM,CO2,DRYCHEMICAL

Unusual Fire and Explosion Hazards  
MATERIAL MAY SPLATTER ABOVE 212 DGS.F.SEALED CONTAINERS MAY EXPLODE WHEN EX-  
POSED TO EXTREME HEAT.

Special Firefighting Procedures  
POLYMER FILM CAN BURN.AVOID BREATHING FUMES,TRACE AMOUNTS OF CARBON DIOXIDE-  
CARBON MONOXIDE MAY BE RELEASED.COOL CONTAINERS WITH WATER.

SECTION V: HEALTH HAZARD DATA

Effects of Overexposure

HEADACHE, NAUSEA, AND IRRITATION OF NOSE, THROAT, AND LUNGS.

Medical Conditions Prone to Aggravation by Exposure

NONE KNOWN

Primary Routes of Entry into the Body, and Effects

INHALATION, SKIN, EYES, AND, SWALLOWING.

EMERGENCY FIRST-AID PROCEDURES

EYE AND SKIN CONTACT: FLUSH EYES WITH LARGE AMOUNTS OF WATER FOR AT LEAST 15 MINUTES. CONSULT PHYSICIAN. WASH AFFECTED AREA WITH SOAP AND WATER. INHALATION: MOVE SUBJECT TO FRESH AIR.

SECTION VI: REACTIVITY DATA

Stability: STABLE Hazardous Polymerization WILL NOT OCCUR.

Hazardous Decomposition Products

CARBON DIOXIDE/CARBON MONOXIDE

Conditions to Avoid

NONE KNOWN

Incompatibilities (Materials to Avoid)

NONE KNOWN

SECTION VII: SPILL OR LEAK PROCEDURES; WASTE DISPOSAL

Steps to be taken if Material is Leaked or Spilled

AVOID CONTACT. SOAK UP WITH ABSORBENT MATERIAL. KEEP SPILLS OUT OF MUNICIPAL SEWERS AND OPEN BODIES OF WATER.

Waste Disposal Methods

DISPOSE OF IN ACCORDANCE WITH FEDERAL, STATE, AND LOCAL REGULATIONS.

SECTION VIII: SAFE HANDLING AND USE INFORMATION

Respiratory Protection

DUST AND MIST MASK SUCH AS TC-21C-141 OR TC-21C-183 FOR PARTICULATE DUST PROTECTION.

Ventilation

MECHANICAL EXHAUST MAY BE REQUIRED IN CONFINED AREAS.

Protective Gloves

RUBBER GLOVES REQUIRED FOR PROLONGED CONTACT.

Eye Protection

GOGGLES CAPABLE OF PROTECTION AGAINST SPLASH OR SPRAY (ANZI Z87 OR EQUAL).

=====  
Other Protective Equipment  
USUALLY NOT REQUIRED.

Hygienic Practices  
NORMAL HYGIENIC PRACTICES SHOULD BE FOLLOWED.

-----  
SECTION IX: SPECIAL PRECAUTIONS

Handling and Storing  
KEEP IN AREA WITH TEMPERATURES NOT BELOW 50 DGS.F.OR ABOVE 100 DGS.F.KEEP  
CONTAINERS LABELED.KEEP OUT OF THE REACH OF CHILDREN.

Other Precautions  
NONE KNOWN.

-----  
Disclaimer:THIS INFORMATION IS BASED ON TECHNICAL DATA BELIEVED TO BE ACCURATE  
AND RELIABLE,BUT IS FURNISHED WITHOUT ANY EXPRESSED OR IMPLIED WARRANTIES.  
=====

END OF MSDS  
=====

**24 Hour Emergency Contact Information:**  
**1 - (800) - 255-3924 U.S.A. & Canada**  
**Outside the U.S.A.**  
**Country Code call originating from then + 01-813-248-0585**